

Cape Cod



Cape Cod makes it easy for every homeowner to enjoy the beauty of this distinguished profile. It provides simple elegance and clean crisp lines for our remodeling or new construction project. Cape Cod, made of .044" premium thick vinyl or polymer for outstanding strength and durability, will provide you with a lifetime of protection for your investment as well as peace of mind for as long as you own your home.

- Available in a unique 3" over 6" profile.
- Creates the authentic look and deep shadow lines usually only found in traditional wood siding.
- Never needs painting.
- Virtually maintenance free.
- Comes with a full Line of accessories
- Made with the Rich-Lock™ Color System.
- Comes with a Lifetime Limited Warranty including fade.

Manufacturer

Materials to be supplied by Continental Manufacturing LLC, 1026 S. Powell, Independence, MO 64055

Materials

All of the vinyl siding shall be extruded Poly Vinyl Chloride (PVC) and shall conform to the following requirements established by ASTM Specifications D 3679, developed in cooperation with the industry and published by the American Society for Testing and Materials.

Typical Compound Properties

Tensile Strength: ASTM D638 6,040 psi
Tensile Modulus: ASTM D638 365,000 psi
Flexural Strength: ASTM D790 11,500 psi
Flexural Modulus: ASTM D790 410,000 psi
Izod 73°F Method A 17.0 ft-lb/in

VSI Flammability

Burn Length (0.040 in Bar) ASTM D635 0* IN. Burn Time (0.040 in Bar) ASTM D635 0* Sec
Drop Dart Impact Resistance Procedure A, 73° F ASTM D4226 1.9 in-lb/mil
Drop Dart Impact Resistance Procedure B, 73° F ASTM D4226 4.0 in-lb/mil
Vulcanizate Properties Hardness Instantaneous, D ASTM D2240 83
Thermal Properties HDT Unannealed, 264 psi ASTM D648 162 °F
Coeff of Linear Thermal Expansion ASTM D696 3.6EO in/in/°F
Gloss: plus or minus 5 units, ASTM D3679
Surface Distortion: No Distortion at 105°F, ASTM D3679
Weatherability: No surface or structural defects when tested as per ASTM D3679

Siding Dimensions and Description

Cape Cod, single 3" over 6" horizontal siding panel, 9 in. wide exposure configured as a 3" panel over a 6" panel, 12' 16'8" & 29' lengths.

Thickness 0.044 in. ±0.002 in.

Embossed Wood Grain: Color to match the samples provided.

Interlock: Siding panels are made with post form style lock with positive interlock.

Both ends of the panel are factory cut and notched for overlap.

Weep holes: Small holes under the bottom butt prevent vapor build up and allow accumulated moisture to escape.

Continental Manufacturing LLC | 1026 S Powell | Independence, MO 64055

Phone: 866-704-3111 | Fax: 816-796-3555 | www.sidingmfg.com